



DESIGN DRA		DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECK	ED 5	APPROVED	D3397	REV. A SHEET 1 OF 3
05.02.10			TITLE WHEEL ASSEMBLY	SCALE 1:8
Α	0;	5.02.10	NEW ISSUE	



WHEEL SPECIFICATIONS					
SIZE	MAXIMUM LOAD	MAXIMUM INFLATATION LOAD			
TIRE:	445 LBS	50 PSI*			

1 D3397-1 TIRE AND RIM ASS'Y



D3397-041 WHEEL ASS'Y

NOTES:

- 1) POSSIBLE SUPPLIER: McMASTER-CARR, P/N 4997T28. SCRAP ORIGINAL BEARING 2) POSSIBLE SUPPLIER: GENERAL BEARING
- 4) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

- 5) ALL DIMENSIONS ARE IN INCHES
 6) INFLATE TIRE TO MAX. 50 psi
 7) APPLY RUST INHIBITOR NOT PROTECTED BY PAINT. RUST INHIBITOR P/N: LPSC30316


COPYRIGHT © 2005 BY DART AEROSPACE LTD.



DESIGN RF	DRAWN BY	DART AEROSPA HAWKESBURY, ONTARIO	
CHECKED	APPROVED	DRAWING NO.	REV. A
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	MIL	D3397	SHEET 2 OF 3
DATE	ν	TITLE	SCALE
05	.02.10	WHEEL ASSEMBLY	1:1



SPECIFICATION CONTROL DRAWING



D3397-3 RETAINER

NOTES:


- 1) MATERIAL: REMOVE FROM McMASTER-CARR P/N 4997T28 AND MODIFY AS SHOWN 2) FINISH: POWDER COAT FIRE RED (REF. 4.3.5.10) PER DART QSI 005 4.3 3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

- 4) ALL DIMENSIONS ARE IN INCHES 5) BREAK ALL SHARP EDGES 0.005 TO 0.025



DESIGN RF	DRAWN BY	DART AEROSPACE HAWKESBURY, ONTARIO	
CHECKED	APPROVED	DRAWING NO.	REV. A
(1)	1 /HY	D3397	SHEET 3 OF 3
DATE	. !	TITLE	SCALE
05	.02.10	WHEEL ASSEMBLY	1:1





D3397-5 SLEEVE

NOTES:

- 1) MATERIAL: AISI 1020-1025 ROUND TUBING PER MIL-T-5066 OR ASTM A513-00 MT1020 SRA OR AMS 5075 OR AMS 5077, COLD DRAWN, SEAMLESS (REF. DART SPEC. M1020TR1.375W.125)

 2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

 3) ALL DIMENSIONS ARE IN INCHES

 4) BREAK ALL SHARP EDGES 0.010 TO 0.025

COPYRIGHT © 2005 BY DART AEROSPACE LTD.